

## Recommendations from the Manufacturer

### Tests of Prime Box polymer packaging:

Before testing the samples, the room should have a temperature of 23°C and a relative humidity of 65% ( $\pm$  5%).

### Transportation of Prime Box polymer packaging:

Transportation of products is allowed by all types of closed vehicles in accordance with the requirements applicable to this type of transport

Do not place anything above of the packed pallets

Fix the products in the vehicle to avoid pallets shifting and tilting

Transport products at temperatures between 1°C and 35°C

### Using Prime Box polymer packaging and filling it with products:

In cases of violation of temperature conditions during transportation (below 1°C and above 35°C), the polymer packaging must be conditioned before use within 24 hours at a temperature of (21 $\pm$ 2)°C

The temperature of the filler product should be less than 75°C

The temperature of the filler product when closing with a lid should be less than 45°C

### Storage of Prime Box polymer packaging:

The products must be stored in a closed, dry room in the absence of acidic, alkaline and other impurities in the air, as well as flammable liquids. Products must be protected from direct sunlight

It is not allowed to store products at a distance of less than 1 m from working heating devices

### Prime Box product packaging:

Packed products are stacked on pallets, pallets or racks. The distance from the floor must be at least 0.1 m.

The pallet must be whole, strong and able to withstand the weight of the products

Stacking of products is allowed only in five rows in height

When placing in five tiers, the last and middle row must be covered with corrugated cardboard. In the hot season, it is recommended to cover each row with corrugated cardboard to improve the stability of the pallet

The maximum static load on the cover and the container in the lower row is calculated at 20°C

The pallet must be completely wrapped in a stretch or shrink film; the film should not deform the products

### Prime Box guarantees:

The manufacturing enterprise guarantees compliance of the quality of the products with the requirements of these technical conditions in compliance with the transportation and storage rules established by these technical conditions.

The warranty period for the products is 12 months from the date of shipment from the manufacturing enterprise.

**IMPORTANTLY!** Storage of more products on a pallet than specified in this document or the technical characteristics of a separate bucket, as well as the effectiveness of using additional packaging materials, must be confirmed by individual tests.